



Contribution ID: 168

Type: **Poster (by default)**

Development of an RF-Driven Ion Source for the KSTAR Neutral Beam Injection System

The current ion sources employed in the KSTAR (Korea Superconducting Tokamak Advanced Research) neutral beam injection system utilize conventional filament-driven multicusp ion sources. However, the primary limitations of this source arise from the usage of 12 tungsten filaments, leading to complexities and maintenance issues. To overcome these drawbacks, the development of an RF-driven ion source has been initiated. In this study, a preliminary performance evaluation was conducted for an inductively coupled plasma source, employing a 5.5 kW RF power supply operating at 13.56 MHz.

To comprehensively characterize the plasmas, plasma diagnostics were conducted using an RF-compensated single Langmuir probe. Moreover, a 2-D plasma modeling utilizing COMSOL was performed, enabling a thorough analysis by comparing the modeling results with experimental data. The integration of experimental measurements and computational simulations offers crucial guidance for the development of the RF ion source, ensuring its compliance with the specific requirements for implementation in the KSTAR neutral beam injection system.

Funding Agency

Email Address

mpark@kfe.re.kr

I have read the Code of Conduct to attend ICIS2023.

Yes

Presenter if not the submitter of this abstract

Primary author: PARK, Min (Korea institute of Fusion Energy)

Co-authors: KIM, Byoungseung (UST-KFE School); NA, Byungkeun (Korea Institute of Fusion Energy); JEONG, Jinhyun (Korea Institute of Fusion Energy); KWAK, Jong-Gu (Korea Institute of Fusion Energy)

Presenter: PARK, Min (Korea institute of Fusion Energy)

Track Classification: Negative Ion Sources and Sources for Fusion Facilities